



EN 13229

BlmSchV Stufe 2

Regensburger BStV / Aachener BStV / Munchener BStV

LRV

4 stelle DM.186 / Conto Termico 2.0



(Max) nominal heat output	13.5 kW
Minimum heat output	6.8 kW
Efficiency at Max	85.1 %
Efficiency at Min	78.9 %
Energy Efficiency Class (A++ / G scale)	A+
Energy Efficiency Index (EEI)	113 %
Seasonal space heating energy efficiency (η_s)	75 %
Temperature of exhaust smoke at Max	198 °C
Temperature of exhaust smoke at Min	227 °C
Particulate/OGC / Nox (nominal at 13%O₂)	27 - 34 - 96 mg/Nm³
CO at 13% O₂ at Min and at Max	0.125 - 0.096 %
CO₂ at Min and at Max	7.3 - 9.2 %
Mass of smoke at Min and at Max	7.7 - 10.7 g/sec
Fuel dimensions	L 250 ÷ 330mm
Hourly consumption at Min and at Max	2 - 3.6 kg/h *
Heatable volume m³	245 - 386 - 675 **
Combustion air inlet	Ø 150 mm
Air inlet	180 cm²
Smoke outlet	Ø 200 mm
Net weight	401 kg
Distance from combustible material (back/side/under)	160 mm / 160 mm / 220 mm
Distance from combustible material (front/ceiling)	800 mm / 1400 mm

* Data that may vary depending on the type of pellets used.

 **Heatable volume based on the requested power per m³ (respectively 55-35-20 W/m³)