



*APERTURA FOCOLARE PER RIVESTIMENTO

- A** SEMITRANCO VENTILAZIONE NATURALE (VN)
- B** SEMITRANCI Ø100-150
- C** INGRESSO ARIA COMBURENTE Ø 150



EN 13229

BlmSchV Stufe 2

Regensburger BStV / Aachener BStV / Munchener BStV

ART.15a B-VG / LRV

4 stelle DM.186



flamme
VERTE

(Max) nominal heat output	13.3 kW
Minimum heat output	6.4 kW
Efficiency at Max	80.1 %
Efficiency at Min	80 %
Energy Efficiency Class (A++ / G scale)	A
Energy Efficiency Index (EEI)	106 %
Seasonal space heating energy efficiency (ηs)	70 %
Temperature of exhaust smoke at Max	271 °C
Temperature of exhaust smoke at Min	177 °C
Particulate/OGC / Nox (nominal at 13%O2)	29 - 69 - 130 mg/Nm3
CO at 13% O₂ at Min and at Max	0.121 - 0.1 %
CO₂ at Min and at Max	7.9 - 9.5 %
Recommended draught at Max power	12 Pa
Minimum draught allowed for minimum power	10 Pa
Mass of smoke at Min and at Max	5.7 - 11.9 g/sec
Fuel dimensions	L 250 ÷ 330mm
Hourly consumption at Min and at Max	1.9 - 3.9 kg/h *
Heatable volume m³	242 - 380 - 665 **
Combustion air inlet	Ø 150 mm
Air inlet	180 cm²
Smoke outlet	Ø 200 mm
Net weight	344 kg
Distance from combustible material (back/side/under)	160 mm / 260 mm / 220 mm
Distance from combustible material (front/ceiling)	800 mm / 2000 mm

* Data that may vary depending on the type of pellets used.

**Heatable volume based on the requested power per m³ (respectively 55-35-20 W/m³)