



EN 16510
 BlmSchV Stufe 2
 Regensburger BStV / Aachener BStV / Munchener BStV
 ART.15a B-VG / LRV
 5 stelle DM.186 / Conto Termico 2.0



(Max) nominal heat output	6 kW
Minimum heat output	2.9 kW
Efficiency at Max	91.1 %
Efficiency at Min	92 %
Energy Efficiency Class (A++ / G scale)	A+
Energy Efficiency Index (EEI)	129 %
Seasonal space heating energy efficiency (ηs)	88 %
Temperature of exhaust smoke at Max	172 °C ***
Temperature of exhaust smoke at Min	111.6 °C ***
PM / OGC / NOx at Max (13% O₂)	14 / 1 / 94 mg/Nm³
PM / OGC / NOx at Min (13% O₂)	8 / 1 / 96 mg/Nm³
CO at 13% O₂ at Min and at Max	0.007 / 0.006 %
CO₂ at Min and at Max	7.2 / 10.7 %
Recommended draught at Max power	10 Pa ****
Minimum draught allowed for minimum power	5 Pa ****
Mass of smoke at Min and at Max	3 / 4.4 g/sec
Hopper capacity	23 l / 15 kg *
Fuel dimensions	Ø6mm L3÷40mm
Hourly consumption at Min and at Max	0.7 / 1.4 kg/h *
Autonomy at Min and at Max	21 / 11 h *
Heatable volume m³	109 / 171 / 300 **
Combustion air inlet	Ø 50 mm
Air inlet	80 cm²
Smoke outlet	Ø 80 mm
Nominal electrical power (EN 60335-1).	14 W (max 386 W)
Supply voltage and frequency	230 Volt / 50 Hz
Net weight	126 kg
Distance from combustible material (back/side/under)	50 / 100 / 0 mm
Distance from combustible material (front/ceiling)	800 / 1000 mm

* Data that may vary depending on the type of pellets used.

**Heatable volume based on the requested power per m³ (respectively 55-35-20 W/m³)

*** Flue gas temperature at the appliance outlet, to be used in the chimney sizing calculation (according to EN 13384-1)

**** Consider a minimum draught of 2 Pa in the EN 13384-1 chimney dimensioning calculations